



NAPOMENA :

- Otvore Ø 12,5 bušiti u alatu
- Varove obrusiti
- Zaštitiiti galvanskim cinkovanjem
- Po mogućnosti sklop raditi iz jednog dela

GSP: 3200817

41-110

| | | | | | | | |
|---|---------|-----------|------------|-------------|--------------|--------------|--------------|
| Ako nije označen stepen tačnosti za sve slobodne mere ostvarene obradom skidanjem strugotine primenjivati izuzetan stepen tačnosti (JUS M.A1.410) | | | | | | | |
| I do 6 | 6 do 30 | 30 do 120 | 120 do 315 | 315 do 1000 | 1000 do 2000 | 2000 do 4000 | 4000 do 6000 |
| ± 0.05 | ± 0.15 | ± 0.2 | ± 0.3 | ± 0.5 | ± 1.2 | ± 2 | ± 3 |

| | | | | | | | |
|---------|--------|--------------------------|----------|---------------|-----------|------|---------------|
| 01 | 009 | NAZIV DETALJA-SKLOPA | Standard | Č.0361 | Dimenzije | Kom. | Težina u kp |
| Montaž | Detalj | | | Materijal | MREŽA-41 | | GSP "BEOGRAD" |
| Veza sa | | | | | | | |
| R 1:1 | | DUPLA KOBILICA "ITALIJA" | | Snimio-konst. | | | TURKALJ G. |
| | | | | Crtao | | | |
| | | | | Pregledao | | | MANČIĆ M. |
| | | | | Overava | | | FENK A. |